


- | ITEM | MATERIAL |
|------|---|
| 1 | CLEAN-OUT RISER, SEE NOTE 1. |
| 2 | 45 DEGREE BEND, LONG-RADIUS SWEEP. |
| 3 | 560-C-3250 CONCRETE COLLAR (ROUND). SEE NOTE 3. |
| 4 | 560-C-3250 CONCRETE COLLAR (SQUARE). |
| 5 | CONSTRUCT FRAME, COVER AND CONCRETE COLLAR PER "PAVED" OR "UNPAVED" CONDITION HEREON. |
| 6 | PRECAST BOX, FRAME AND COVER WITH MARKING AS SHOWN HEREON. ALHAMBRA #A-1240, NEENAH #R-1976, OR APPROVED EQUAL. |
| 7 | SOLVENT WELD x FIPT SCH. 40 ADAPTER. |
| 8 | PVC SCH. 40 STOPPER. MIPT PLUG WITH MALE SQUARE NUT. |
| 9 | 3/4-INCH DIA. CRUSHED ROCK. |
| 10 | AGGREGATE BASE. |

- NOTES:**
1. CONSTRUCT CLEANOUTS OF THE SAME DIAMETER (4", 6" OR 8") AND MATERIAL AS THE SEWER LATERAL.
 2. USE SDR 35 PIPE AND FITTINGS WHERE COVER OVER PIPE EXCEEDS 5 FEET AND SDR 26 WHERE COVER IS 5 FEET OR LESS.
 3. IF LOCATED IN CONCRETE PAVEMENT, CONSTRUCT 6-INCH THICK ROUND COLLAR FLUSH WITH PAVEMENT.
- NOT TO SCALE

SEWER LATERAL TERMINAL CLEANOUT

REVISION			APPROVED:		7/16/2018		CITY OF CORONA
NO.	APPROVED	DATE	<i>Nelson D Nelson</i> NELSON D. NELSON, PE, PUBLIC WORKS DIRECTOR		DATE		STD 307
1	VRW	07/16/18	<i>Vernon R. Weisman</i> VERNON R. WEISMAN, PE, DISTRICT ENGINEER		7/16/2018	SHEET 1 OF 1	
					DATE		