


### TYPICAL SECTION

#### NOTES:

1. THICKNESS OF PAVEMENT SECTION TO BE DETERMINED BY R-VALUE TESTING PER CALTRANS DESIGN METHOD WITH RECOMMENDED SAFETY FACTOR, MINIMUM 0.33' AC / 0.50' AB.
2. MINIMUM TRAFFIC INDEX = 5.
3. HALF WIDTH STREETS SHALL BE CONSTRUCTED TO A WIDTH OF 1/2 STREET WIDTH PLUS 10'.
4. MAXIMUM LENGTH OF LOW VOLUME LOCAL STREET SHALL BE 500 FEET OR AS APPROVED BY THE PUBLIC WORKS DIRECTOR.
5. LOW VOLUME LOCAL STREET MAY ONLY BE USED FOR STREETS NOT SUBJECT TO FUTURE CONTINUATION, AND STREETS WITH A MAXIMUM PROJECTED A.D.T OF 250.
6. LOW VOLUME LOCAL STREETS MAY ONLY BE USED ON A CASE-BY-CASE BASIS AFTER REVIEW AND APPROVAL BY THE PUBLIC WORKS DIRECTOR.



APPROVED BY:  
*Kip D. Field* 11/23/09  
CITY ENGINEER DATE  
KIP D. FIELD

CITY OF CORONA

LOW VOLUME LOCAL STREET

REVISION	DESCRIPTION	BY	DATE

STANDARD PLAN NUMBER: 108 SHT 1 OF 1