

## NOTES:

- 1. TRAFFIC SIGNAL CONDUIT & PULL BOXES SHALL BE CONSTRUCTED AT ALL NEW OR RECONSTRUCTED INTERSECTION OF ANY MAJOR, SECONDARY, OR COLLECTOR STREET WITH ANY OTHER MAJOR, SECONDARY OR COLLECTOR STREET (WITHIN THE LIMITS OF CONSTRUCTION).
- 2. ALL PULL BOXES SHALL BE NO. 6 UNLESS OTHERWISE SPECIFIED BY CITY'S ENGINEER.
- ALL CONDUIT SHALL BE 3" SCHEDULE 80 PVC WITH PULL ROPE AND NO. 10 GREEN INSULATED CONDUCTOR WIRE AS A LOCATOR WIRE OR 3" RIGID GALVANIZED WITH PULL ROPE UNLESS OTHERWISE SPECIFIED BY CITY'S ENGINEER.

PROFESS/ONA	APPROVED BY:  11/23/09  CITY ENGINEER  KIP D. FIELD		CITY OF CORONA		
No. C 45679 ₹ 5xp. 12-31-10				TRAFFIC SIGNAL CONDUIT LOCATION	
OF CALIFORNIE	REVISION DESCRIPTION	BY	DATE	STANDARD PLAN NUMBER: 509	SHT 1 OF 1