


| MAIN LINE & CONTROL WIRES UNDER PAVING |     |    |
|--|-----|----|
| DIMENSION                              | A   | B  |
|  | 24" | 4" |


| LATERAL PIPES                |     |
|------------------------------|-----|
| DIMENSION                    | A   |
| ROTARY HEADS MIN. 3/4" INLET | 18" |
| ALL OTHER HDS.               | 12" |

| MAIN LINE & CONTROL WIRES IN AVERAGE SOIL CONDITION |     |
|---|-----|
| DIMENSION (PIPE)                                    | A   |
| 1/2" TO 3" SIZE                                     | 18" |
| 4", 6" & 8" SIZE                                    | 24" |

'A' IS MEASURED BELOW AGGREGATE BASE OF PAVING.

NOTE: TRENCHES TO BE WIDE ENOUGH TO ALLOW 4" MIN. HORIZONTAL CLEARANCE BETWEEN PARALLEL PIPES. COMPACT TRENCH BACKFILL TO COMPACTION SAME AS ADJACENT AREAS AND TO 90% COMPACTION IN PAVED AREAS



APPROVED BY:  
  
 CITY ENGINEER  
 KIP D. FIELD

11/23/09  
 DATE

CITY OF CORONA

LANDSCAPE TRENCHING

| REVISION | DESCRIPTION | BY | DATE |
|----------|-------------|----|------|
|          |             |    |      |

STANDARD PLAN NUMBER: 601

SHT 1 OF 1