

- BACKGROUND SHALL BE PAINTED WITH GOOD QUALITY HIGH GLOSS REFLECTIVE WHITE PAINT. REFLECTIVE WHITE PAINT PAINT SHALL BE "PRE-MIX."
- 2. NUMBERS SHALL BE PAINTED WITH GOOD QUALITY FLAT BLACK PAINT.
- 3. THE TOP OF THE NUMBERS SHALL BE ONE (1) INCH BELOW THE TOP OF THE CURB.
- 4. NUMBERS SHALL BE PLACED WITHIN TWO (2) FEET OF THE DRIVEWAY, ON THE SIDE OF THE DRIVEWAY CLOSEST TO THE FRONT DOOR OF THE HOUSE. IF THERE ARE EXISTING NUMBERS, THE NEW NUMBERS SHALL BE PAINTED OVER THEM.
- 5. IF THERE IS NO DRIVEWAY, THE NUMBERS SHALL BE PAINTED ON THE CURB FACE IN FRONT OF THE MAIN ENTRANCE.
- 6. ALL WORK SHALL BE SUBJECT TO INSPECTION BY CITY PERSONNEL FOR ACCURACY, COMPLETENESS, AND WORKMANSHIP. ANY DEFICIENCIES NOTED SHALL BE PROMPTLY CORRECTED BY THE PERMITTEE.

PROFESS/ONA	APPROVED BY:  11/23/09  CITY ENGINEER  KIP D. FIELD			CITY OF CORONA		
No. C 45679  Exp. 12-31-10  OF CALLED				CURB PAINTING		
	REVISION	DESCRIPTION	BY	DATE	STANDARD PLAN NUMBER:	710