


PARKWAY UTILITY TRENCH

NOTES

1. ALL TRENCHES SHALL BE BACKFILLED, COVERED WITH TRENCH PLATES OR OTHER MATERIAL AS APPROVED BY THE PUBLIC WORKS INSPECTOR, OR FENCED AT THE END OF EACH WORK DAY AS DIRECTED BY THE PUBLIC WORKS INSPECTOR.
2. REPAIR OR REPLACE ANY DAMAGED OR ALTERED IMPROVEMENTS (INCLUDING LANDSCAPE, IRRIGATION AND SIDEWALK) AS DIRECTED BY THE PUBLIC WORKS INSPECTOR.
3. WINDOWS AND/OR NARROW TRENCH CUTS SHALL NOT BE ALLOWED IN EXISTING P.C.C IMPROVEMENTS. SIDEWALKS SHALL BE CONSTRUCTED IN PANELS EQUAL TO EXISTING FINISH AND SCORE LINES (4'X4' OR 5'X5' TYP). DRIVEWAY APPROACHES AND ALLEY APPROACHES SHALL BE SAW-CUT AND REPLACED AS DIRECTED BY THE PUBLIC WORKS INSPECTOR.



APPROVED BY:

 CITY ENGINEER
 KIP D. FIELD

11/23/09
 DATE

CITY OF CORONA

PARKWAY UTILITY TRENCH

REVISION	DESCRIPTION	BY	DATE

STANDARD PLAN NUMBER: **149** SHT 1 OF 1