

PLANTING


1. PARKWAYS


- A. STREET TREES SHALL BE PLANTED IN STRICT CONFORMANCE TO CITY STANDARD PLANS 614, 615, 616, AND 617.
- B. STREET TREES SHALL BE DETERMINED AND ASSIGNED AT THE TIME OF THE DPR REVIEW BY THE PARKS AND COMMUNITY SERVICES DEPARTMENT.
- C. TURF TYPE TALL FESCUE SOD MAY BE REQUIRED IN ALL PARKWAYS. EXCEPTIONS AND SUBSTITUTIONS MUST BE APPROVED BY THE DIRECTOR OF PARKS AND COMMUNITY SERVICES PRIOR TO PLAN SUBMITTAL.
- D. ALL STREET TREES SHALL HAVE A MINIMUM OF 1" TRUNK CALIPER, 4' ABOVE THE GROUND, AND SHALL BE 24" BOX MINIMUM.
- E. PARKWAYS SHALL BE GRADED 1/2" BELOW CONCRETE AT SIDEWALK AND SLOPE 2% TOWARD CURB.

2. SLOPES & PLANTERS

- A. ALL CFD/LMD'S SHALL CONTAIN PLANTINGS OF TREES AND SHRUBS.
- B. TREES SHALL BE PLANTED AT A RATE OF 2 - 24" BOX AND 1 - 15 GAL SIZE PER 1,000 SQUARE FEET. THE CITY REPRESENTATIVE IN THE FIELD MAY REDUCE THIS NUMBER BASED ON ACTUAL CONDITIONS.
- C. 5 GALLON SHRUBS SHALL BE IN LARGE SWEEPING MASS PLANTINGS. THEY ARE TO BE INSTALLED IN TRIANGULAR PATTERN AT THE RADIUS OF SHRUB WIDTH.
- D. A 3" LAYER OF MEDIUM GRIND MULCH IS TO BE APPLIED THROUGHOUT ALL LMD/CFD PLANTING AREAS. SUBMITTAL TO BE APPROVED BY CITY INSPECTOR. HYDROSEED MAY BE SUBSTITUTED FOR MULCH WITH WRITTEN APPROVAL OF THE PARKS AND COMMUNITY SERVICES DIRECTOR.
- E. ALL STREET TREES WITHIN CFD/LMD'S SHALL BE 30' - 40' O.C. AND FROM THE APPROVED STREET TREE LIST.
- F. ALL TREES WITHIN CFD/LMD'S SLOPES SHALL BE PLANTED IN ACCORDANCE WITH CITY STANDARD DETAIL 618. ROOT PANELS SHALL BE REQUIRED FOR ALL TREES CLOSER THAN 6 (SIX) FEET TO HARDSCAPE.
- G. NO SHRUBS OR TREES SHALL BE PLANTED CLOSER THAN DIAMETER OF PLANT WIDTH TO ANY SIDEWALKS, "V" DITCHES, WALLS OR PEDESTALS UNLESS OTHERWISE DICTATED BY BY FIELD CONDITIONS AND APPROVED BY PARKS AND COMMUNITY SERVICES DIRECTOR.
- H. NO SHRUBS OR TREES SHALL BE PLANTED CLOSER THAN ITS DIAMETER AT MATURITY TO ANY WALLS, FENCES, SIDEWALKS, PEDESTALS OR OTHER LIKE IMPROVEMENTS UNLESS DICTATED BY FIELD CONDITIONS AND APPROVED IN WRITING BY THE DIRECTOR OF PARKS AND COMMUNITY SERVICES OR HIS/HER DESIGNEE.

(TO BE PLACED ON
ALL CFD/LMD PLANS)



APPROVED BY:

 11/23/09
 CITY ENGINEER DATE
 KIP D. FIELD

CITY OF CORONA

PLANTING NOTES

REVISION	DESCRIPTION	BY	DATE

STANDARD PLAN NUMBER: **628** SHT 1 OF 2

PLANTING (CONTINUED)

- I. TREES MUST BE SPACED SO THEY WILL NOT OVERLAP AT MATURITY.
- J. ALL SOIL NEXT TO CURBS AND SIDEWALKS SHALL BE GRADED AT 1" BELOW THE FINISHED SURFACE.
- K. ALL SLOPE SHRUB AND TREE PLANTING LOCATIONS SHALL BE APPROVED BY THE PARKS AND COMMUNITY SERVICES DEPARTMENT PRIOR TO INSTALLATION.
- L. HYDROSEED MIX TAGS SHALL BE SUBMITTED TO THE PARKS AND COMMUNITY SERVICES DEPARTMENT PRIOR TO APPLICATION.
- M. ALL PLANTED MATERIAL SHALL BE LUSH, VIGOROUS, FULL AND IN HEALTHY CONDITION PRIOR TO ACCEPTANCE BY THE CITY.
- N. SOIL AMENDMENTS SHALL BE ADDED TO ALL PLANTING AREAS WITH GRADIENTS 3:1 AND LESS. (AGRONOMIC SOIL TEST SHALL RECOMMEND SPECIFIC AMOUNTS, SEE CITY STANDARD PLAN 626 "SOIL PREPARATION NOTES")
- O. PRIOR TO DESIGNING THE PLANTING, ALL LANDSCAPE ARCHITECTS SHALL OBTAIN A COPY OF THE SOILS REPORT AND GUARANTEE THAT NO EXCESSIVE SALTS, BORON OR OTHER TOXINS EXIST WITHIN THE PROPOSED PLANTING AREAS.
- P. MULCH SAMPLES MUST BE APPROVED BY THE PARKS & COMMUNITY SERVICES DEPARTMENT PRIOR TO APPLICATION

(TO BE PLACED ON
ALL CFD/LMD PLANS)



APPROVED BY:			
			11/23/09
CITY ENGINEER			DATE
KIP D. FIELD			
REVISION	DESCRIPTION	BY	DATE

CITY OF CORONA	
PLANTING NOTES	
STANDARD PLAN NUMBER: 628	SHT 2 OF 2